



Product Model Number

CKO-SA17-045021-1311

✓ Model Number Definitions

CKO-XXXX-XXXXXX-XXXX




- A. Chun Kuang Optics Corp. Product
- B. Product Type: product abbreviation
Ex:
CH→CoB High Intensity
CC→CoB Compact
CS→Soft Shading for CoB LED
HC→Holder for CoB LED

- C. Identity Code
- D. Lens / Fixture Size
Ex: 075026=Φ75mm / Thickness=26mm (round up)
- E. Serial Numbers

The lens datasheet is applicable for **Philips LED**, that manufactured by Chun Kuang Optics Corp.

✓ Dimensions (mm) : Φ45 x 20.9




▽:Critical Dimension




Optical Characteristics

Model Number	CKO-SA17-045021-1311		
LED	Fortimo SLM 1202 L06 G7		
LES / LED Size	Φ 6.5 mm		
FWHM (D50)	28°x37°		
Field Angle (D10)	52°x75°		
H (distance)	2.5 mm		
Dimension	Φ =45 mm, Thickness=20.9 mm		
Luminous Flux	905 lm	Measured @ 7 W	
Material	PC / UL94V2		

cd/klm



Illuminance At Distances







Optical Characteristics

Model Number	CKO-SA17-045021-1311		<p>"H" definition</p>
LED	Fortimo SLM 1202 L06 G6		
LES / LED Size	Φ 6.5 mm		
FWHM (D50)	29°x37°		
Field Angle (D10)	51°x75°		
H (distance)	2.5 mm		
Dimension	Φ =45 mm, Thickness=20.9 mm		
Luminous Flux	867 lm	Measured @ 7.0 W	
Material	PC / UL94V2		

cd/klm



Illuminance At Distances







Optical Characteristics

Model Number	CKO-SA17-045021-1311		<p>"H" definition</p>
LED	Fortimo SLM 1203 L09 G6		
LES / LED Size	Φ 9 mm		
FWHM (D50)	32°x39°		
Field Angle (D10)	57°x79°		
H (distance)	2.5mm		
Dimension	Φ =45 mm, Thickness=20.9 mm		
Luminous Flux	1216 lm	Measured @ 10.4 W	
Material	PC / UL94V2		

cd/klm



Illuminance At Distances







Optical Characteristics

Model Number	CKO-SA17-045021-1311		<p>"H" definition</p>
LED	Fortimo SLM C 1203 L09 1619 G6_DL		
LES / LED Size	Φ 9 mm		
FWHM (D50)	30°x39°		
Field Angle (D10)	60°x79°		
H (distance)	3.5mm		
Dimension	Φ =45 mm, Thickness=20.9 mm		
Luminous Flux	1164 lm	Measured @ 10.4 W	
Material	PC / UL94V2		

cd/klm



Illuminance At Distances







Optical Characteristics

Model Number	CKO-SA17-045021-1311		<p>"H" definition</p>
LED	Fortimo SLM C 1203 L09 1619 G6_PI		
LES / LED Size	Φ 9 mm		
FWHM (D50)	30°x39°		
Field Angle (D10)	60°x79°		
H (distance)	3.5mm		
Dimension	Φ =45 mm, Thickness=20.9 mm		
Luminous Flux	1164 lm	Measured @ 10.4 W	
Material	PC / UL94V2		

cd/klm



Illuminance At Distances







Optical Characteristics

Model Number	CKO-SA17-045021-1311		<p>"H" definition</p>
LED	Fortimo SLM PW 1204 L09 G7		
LES / LED Size	Φ 9 mm		
FWHM (D50)	32°x40°		
Field Angle (D10)	58°x80°		
H (distance)	2.5mm		
Dimension	Φ =45 mm, Thickness=20.9 mm		
Luminous Flux	2067 lm	Measured @ 21.6 W	
Material	PC / UL94V2		

cd/klm



Illuminance At Distances







Optical Characteristics

Model Number	CKO-SA17-045021-1311		
LED	Fortimo SLM 1201 L09 G7N		
LES / LED Size	Φ 9.8 mm		
FWHM (D50)	34°x39°		
Field Angle (D10)	59°x80°		
H (distance)	2.5mm		
Dimension	Φ =45 mm, Thickness=20.9 mm		
Luminous Flux	454 lm	Measured @ 3.0 W	
Material	PC / UL94V2		

cd/klm



Illuminance At Distances







Optical Characteristics

Model Number	CKO-SA17-045021-1311		<p>"H" definition</p>
LED	Fortimo SLM 1202 L09 G7N		
LES / LED Size	Φ 9.8 mm		
FWHM (D50)	34°x40°		
Field Angle (D10)	61°x80°		
H (distance)	2.5mm		
Dimension	Φ =45 mm, Thickness=20.9 mm		
Luminous Flux	891 lm	Measured @ 6.1 W	
Material	PC / UL94V2		

cd/klm



Illuminance At Distances






Optical Characteristics

Model Number	CKO-SA17-045021-1311		<p>"H" definition</p>
LED	Fortimo SLM 1203 L09 G7N		
LES / LED Size	Φ 9.8 mm		
FWHM (D50)	35°x41°		
Field Angle (D10)	64°x82°		
H (distance)	2.5mm		
Dimension	Φ =45 mm, Thickness=20.9 mm		
Luminous Flux	1330 lm	Measured @ 9.2 W	
Material	PC / UL94V2		

cd/klm



Illuminance At Distances

